


FARMER III



Use: Light fitting for the illumination of indoor and outdoor industrial spaces. The light fitting is uncompensated.

Technical description:

The light fitting consists of a ballast box – an AlSi alloy casting and a body made of steel sheet, finished with powder paint. The inorganic glass cover with a seal and protective polycarbonate basket is fixed to the body with four stainless steel caps. The max. cross-section of connecting conductors is 4 mm².

Installation:

On the ceiling, with a suspension eye ø30 mm.

Versions:

Version with a protective steel basket – version „K“.

To order:



Glass cover
232.5068/1



Protective basket
182.5005 - PMMA
132.2540 - polycarb.



Protective steel
basket 1-99.6248



Stainless metal
cap 4-99.6180/01

CE	⊕	IP54	E27
Ta -25°C ÷ +55°C (t) -40°C ÷ +40°C (F)		VVG 	230V 50Hz
Carton (mm/pcs): 650 x 280 x 290 / 1			

Type	Recommended light source [W]	Weight[kg]
54118 01 t	High-pressure mercury discharge lamp HQL 125	7,1
54118 02 t	High-pressure sodium/halide discharge lamp 70	7,1
54118 03 F	Halogen lamp HCI-E 150	7,5
54118 04 F	Halogen lamp HQL-E 100	7,5

*By adding the letter „K“ after the type designation, the light fittings will be provided with protective baskets (54118 01Kt).

JUNIOR



Use: Light fitting for the illumination of heavy indoor and outdoor industrial spaces with a high level of mechanical stress.

Technical description:

The light fitting body and flange are AlSi alloy castings finished with powder paint. The optical cover is made of tempered glass. There are two cable outlets on the light fitting sides. There is electrical equipment and a reflector built inside the light fitting. The light fitting is designed as a through light fitting, for three-phase connection (five-core cable). When the light fitting is used as a terminal light fitting, the free cable outlet is blinded with a plug. The max. cross-section of the connecting conductors is 4 mm².


Installation:

With a suspension eye ø19 mm, ceiling holder 4-99.7995, flexible suspension 2-99.5550.

To order:



Shade
254.5021/01



Protective basket
2-99.6195



Flexible suspension
2-99.5550



Protective glass
332.5018



Ceiling holder
4-99.7995

CE	⊕	IP66	230V 50Hz
E27	VVG	Ta -40°C ÷ +50°C (t)	
Carton 410 x 240 x 240 / 1 (mm/pcs): 430 x 240 x 240 / 1 K			

Type	Recommended light source [W]	Voltage [V/Hz]	Weight [kg]
51114 07	Halogen bulb Philips EcoClassic 140	230/50	5
	Bulb CLAS 200	230/50	5
	Blended lamp HWL 160	230/50	5
	**High-pressure mercury discharge lamp HQL 180	230/50	5
	***High-pressure mercury discharge lamp HQL 125	230/50	5

*By adding the letter „K“ after the type designation, the light fittings will be provided with protective steel baskets (51114 07K).

**Light fitting provided with a mercury discharge lamp HQL 80W requires a ballast box type BOX 2.

***Light fitting provided with a mercury discharge lamp HQL 125W requires a ballast box type BOX 2.